



Simple Bottle Installation



SmartValve™ Product Selection



Easy One Handed Low Flow
Bottle Filling



Remote High Flow
Bucket/Autoscrubber Fill Gun



QUATTROSELECT™/MC

The new QuattroSelect™ was designed from the ground up to offer improved...ease of use, reliability, safety, and productivity.



J-Fill™ QuattroSelect™ ... The Best Just Got Better

- SmartValve™**
 QuattroSelect™ is equipped with the US Patent Pending SmartValve™ selector...Making dilution control easier and faster. Simply turn the SmartValve™ selector to the desired product and begin filling. The SmartValve™ selector automatically selects either low flow bottle filling or high flow bucket/autoscrubber filling...**all in one operation.**
- Easy Bottle Filling**
 QuattroSelect™ features low flow, one handed trigger bottle filling...**making low foam filling simple and easy.**
- Bucket/Autoscrubber Fill Gun**
 QuattroSelect™ features a remote filling gun with an 8' hose that permits high flow bucket/autoscrubber filling...**allowing filling control at the gun.**



JohnsonDiversey
Clean is just the beginning





Hose Gun Trigger Lock



8

Easy Service: Toolless Repair with Quick Connect Manifold Removal and Replacement



- 1 Locking Door
- 2 Powder Coated Steel Doors
- 3 Durable ABS Molded Cabinet
- 4 One Handed Low Flow Bottle Fill
- 5 Remote High Flow Bucket Fill with 8' Hose and Gun
- 6 Product Identification Window
- 7 SmartValve™ Product Selector
- 8 Accurate and Reliable Manifold with Safe Gap™ Back Flow Protection
- 9 Water In-Let Hose with Filter Valve
- 10 Removable Drip Tray with Drainage Hose
- 11 Ergonomic Design: User Controls in Yellow



- Check with local backflow regulations
- J-Gap Air Gap Version #0000000 also available

Specifications:

- **Unit Dimensions:** 24.25" x 18.5" x 7.5"
(62 cm x 47 cm x 19 cm)
- **Weight:** 15 lbs (6.8 kg)
- **Weight in Carton:** 19 lbs (8.6 kg)
- **Carton Dimensions:** 27" x 20.5" x 9.5"
(68.6 cm x 52.1 cm x 24.1 cm)
- **Operating Range Requirements:**
 - Water Pressure:** 30 - 85 psi (170 - 580 KPA)
 - Water Flow:** <2.0 gpm (7.6 l/m)
 - Water Temperature:** 50 - 100 °F (10 - 40°C)
- **Low Flow Rate:** 1.5 gpm (5.7 l/m)
- **High Flow Rate:** 3.1 gpm (11.8 l/m)
- **Water In-Let Hose:** 4' (1.22 m)
- **Remote Bucket Fill Hose:** 8' (2.44 m)
- **Drip Tray Drainage Hose:** 8' (2.44 m)
- **QuattroSelect™ Item #:** 3754220

FOR COMMERCIAL & INDUSTRIAL USE ONLY
 © 2005 JohnsonDiversey, Inc., Sturtevant, WI 53177-0902.
www.johnsondiversey.com

Printed in the U.S.A. on recycled paper from 50% total recycled fiber containing 10% post consumer wastes.

To contact your JohnsonDiversey representative call:
 US: 800 626 5015 / Canada: 800 668 7171 / Puerto Rico: 800 959 1533

0000000 SPC000 (05/269)

